

Mission Valley Power Energy Efficient Insulation Program

			Date/_	/	
Account #	Loca	ation #			
Name:	me:				
Address:		Phone			
City	Sta	ate	Zip		
Site Address where inst	talled:				
Address:		Phone	<u> </u>		
New Construction:	□Yes □No	□Ad	ldition [Remodel	
Heating Source:	Electric	1 Propane Wo	ood Othe	r	_
Crawl Space Exterior Wall Ceiling/Attic	Existing RExisting RExisting R	Installed R-Val	ue ue	SF= SF= SF=	
_	•	iome's main heat so y heat sources are a		oe some form of	lelectric
Sq. Ft of Crawlspace I	nsulation:S	SF X \$ =	= \$		
Sq. Ft. of Ext. Wall Ins Sq. Ft. of Ceiling/Attic	sulation: S Insulation: S Tota	SF X \$ = SF X \$ = I Credit Amount Due :	= \$ = \$ = \$		
Include the following					
- Must incl. copy of i contractor w/R Valu	insulation receipt ones, square foot of i	of purchase includin	ng retailer o	-	
- Must incl. before a	-				
		installed at the above add stration to verify installar			
Buyer Signature					
Utility Representativ	ve Signature				

st Allow up to 8 weeks for the billing credit to be applied to your account after receiving completed form and documentation.

Residential Insulation

Requirements and Specifications

This measure is available for all types of existing residential buildings (singlefamily, manufactured and multifamily) electrically heated. Final installed R-values for a reportable measure must meet the required final R-value at a minimum.

Single-Family Attic

R-0 to R-7 R=0 to R-38 or R-49

R-8 to R-11 R=11 to R-38 or R-49

R-12 to R-19 R=19 to R-38 or R-49

R-20 to R-30 R=30 to R-38 or R-49

R-31 to R-38 = R-38 to R-49

Floor R-0 to R-11= R-0 to R-19, R-25, or R-30

R-12* to R-19 = R-19 to R-30

Wall No insulation present R-0 to R-11

Manufactured Home

Attic

R-0 to R-7 = R-0 to R-22 or maximum possible

R-0 to R-11 = R-0 to R-30 or maximum possible

R-12 to R-17 = R-11 to R-30 or maximum possible

Floor

R-0 to R-7 = R-0 to R-11, R-22 or maximum possible

R-8 to R-11 = R-11 to R-22 or maximum possible

*Precondition definitions were modified for consistency across building types, where possible.